



STANDARD INSPECTION LIST



CATEGORY 4

Hull no.: _____ Sail no.: _____

Name of Yacht: _____

BELOW DECK

RULE	ITEM TO CHECK	Answer Yes/No
3.23.5 (b)	1 manual bilge pump	
3.23.5 (f)	2 buckets of stout construction of at least 9 liters, with lanyard	
3.29.1 e)	A hand-held marine VHF transceiver, watertight or with a watertight cover.	
3.29.1 f)	Radio receiver capable of receiving weather bulletins	
4.03	Soft wood plugs tapered and attached to the appropriate fitting	
4.05	At least two fire extinguishers readily accessible in suitable and different parts of boat	
4.06.1	1 anchor readily accessible	
4.07.1 a) 4.23.2 a)	Flashlight watertight. Spare batteries and bulbs	
4.08.1	First aid kit and manual	
4.09	Fog horn	
4.10	Radar reflector. If octahedral, diagonal not less than 456 mm.	
4.16	Tools and spare parts. Means to disconnect or sever the standing rigging	
4.17	Yacht's name on buoyant equipment (lifejackets, lifebuoys, etc.)	
4.18	Retro-reflective material on lifejackets, lifebuoys, liferafts and lifeslings	
4.23.2 b)	Watertight, high-powered white spotlight (searchlight) with spare batteries and bulbs	
4.26.4 c)	Storm trysail or mainsail reefing to reduce luff 40%	
5.01.1/5.01.2	Lifejacket for each crew member as per OSR 5.01.1 & .2	No:

AT CHART TABLE

RULE	ITEM TO CHECK	Answer Yes/No
	Measurement certificate H8	
3.24.1	Compass deviations	
4.10	Radar reflector data (10 m2 cross section if not octahedral)	
4.11	Charts (not solely electronic), light list and chart plotting equipment	
4.12	Durable stowage chart displayed where it can best be seen, clearly marked with the location of the principal items of safety equipment	



ON DECK

RULE	ITEM TO CHECK	Answer Yes/No
3.14.2 a)	Lifelines required in Special Regulations shall be "taut". As a guide, when deflecting force of 50 N (5.1 kgf) is applied to a lifeline midway between supports, the lifelines shall not deflect more than 50 mm	
3.14.3	Complete double lifeline enclosure. Height according to table. Stanchions interval not less than 2.13 m. Upper rails of bow pulpit closed	
3.24.1 a)	1 marine magnetic compass , independent of any power supply, permanently installed and adjusted	
3.27.	Test navigation lights . Spare bulbs (see table). Height not less than upper lifeline	
4.22.1 a)	Lifebuoy with: drogue (or lifesling without drogue), self igniting light, retro-reflective and yacht's name within reach of helmsman and ready for instant use. When inflatable, shall be tested or serviced in accordance with its manufacturer's instructions	
4.24	Heaving line 15 m. minimum length, readily accessible to cockpit	

PYROTECHNIC SIGNALS (Rule 4.23)

ITEM	EXPIRING DATE	CONDITION (G/F/P) (*)
4 RED HAND FLARES 4.23 Pyrotechnic signals	1	
	2	
	3	
	4	
2 ORANGE SMOKE 4.23 Pyrotechnic signals	1	
	2	

(*): G (good), F (fair), P (poor)

Owner: _____

declares that he has checked all items of present list and they are as expressed above.

Signature: _____ Date: _____